

Typ	Gesamtinhalt [in Liter]	Vor- druck [in bar]	Betriebs- über- druck [in bar]	Abmessungen [in mm]				An- schluss D	Ge- wicht [kg]
				Ø A	B	Ø C	E		
Contra-Flex 8	8	1,5	3	245	304	-	-	R 3/4"	2,2
Contra-Flex 12	12	1,5	3	286	336	-	-	R 3/4"	2,7
Contra-Flex 18	18	1,5	3	328	328	-	-	R 3/4"	3,7
Contra-Flex 25	25	1,5	3	358	380	-	-	R 3/4"	4,5
Contra-Flex 35	35	1,5	3	396	439	263	94	R 3/4"	5,4
Contra-Flex 50	50	1,5	6	437	495	263	110	R 3/4"	11,2
Contra-Flex 80	80	1,5	6	519	551	360	142	R 1"	15,0
Contra-Flex 100	100	2,5	6	484	780	360	-	R 1"	23,8
Contra-Flex 150	150	2,5	6	484	1024	360	-	R 1"	27,6
Contra-Flex 200	200	2,5	6	484	1300	360	-	R 1"	38,1
Contra-Flex 250	250	2,5	6	600	1153	360	-	R 1"	51,7
Contra-Flex 300	300	2,5	6	600	1335	450	-	R 1"	56,9
Contra-Flex 350	350	2,5	6	790	1027	450	-	R 1"	69,0
Contra-Flex 400	400	2,5	6	790	1180	610	-	R 1"	76,4
Contra-Flex 500	500	2,5	6	790	1330	610	-	R 1"	83,7
Contra-Flex 600	600	2,5	6	790	1538	610	-	R 1"	92,9
Contra-Flex 800	800	2,5	6	790	1888	610	-	R 1"	126,9
Contra-Flex 1000	1000	2,5	6	790	2268	610	-	R 1"	145,9



8 - 25 Liter



35 - 80 Liter



100 - 1000 Liter