



TECHNISCHE DATEN

		Typ	200	300	500	600	825	1000	1000	1150	1500	2000	2500	3000	5000
Nenninhalt*		Ltr.	207	291	476	598	810	962	951	1098	1484	1908	2411	2852	4816
Durchmesser ohne Isolierung		mm	500	650		790		850		990	1100	1200	1250	1600	
Durchmesser mit Isolierung		mm	700	850		990		1050		1190	1300	1400	1450	1800	
Höhe ohne Isolierung		D mm	1280	1235	1635	1895	1745	2045	1765	2025	2174	2161	2310	2608	2820
Höhe mit Isolierung		mm	1330	1285	1685	1945	1795	2095	1815	2075	2224	2211	2360	2658	2870
Kippmaß		mm	1248	1310	1655	1909	1776	2086	1788	2061	2238	2235	2359	2650	2915
Gewicht		kg	74	123	157	167	169	204	204	282	319	373	350	390	650
Isolationsstärke		mm	100												
zul. Betriebsüberdruck	Heizwasser	bar	3												
Prüfdruck		bar	6												
zul. Betriebstemperatur	Heizwasser	°C	95												
Muffen 6/4"	A		206	195	210	225	289	305	300	315	345	364	390	385	495
	B		586	595	600	691	680	785	690	781	841	844	903	995	1105
	C		961	995	990	1158	1070	1265	1080	1248	1339	1324	1417	1610	1720
	F				1380	1625	1460	1745	1470	1715	1836	1804	1930	2215	2325
Entlüftung		D	5/4" IG												
Bereitschafts-Wärmeaufwand (DIN EN 12897)		W/h	75	83	95	104	117	140	140	145	166	187	204	220	305

* abzgl. Einbauten